

WaStop® Inline Check Valve Technical Specification Stainless Steel AISI 304/316


Model no.:	WS1040-S2-304/316 WS1040-S3-304/316 WS1040-S4-304/316
Nominal Size:	1050 mm
Pipe:	Stainless Steel AISI 304/316
Membrane:	Polyurethane
Fasteners:	Marine grade stainless steel (AISI 316)

Technical data:	Soft (S2)	Standard (S3)	Hard (S4)
Max. back pressure*:	3 mH ₂ O	5 mH ₂ O	8 mH ₂ O
Horizontal opening pressure*:	505 mmH ₂ O	580** mmH ₂ O	650** mmH ₂ O
Horizontal closing pressure*:	313 mmH ₂ O	360** mmH ₂ O	403** mmH ₂ O
Submerged opening pressure*:	196** mmH ₂ O	226** mmH ₂ O	245** mmH ₂ O
Submerged closing pressure*:	116** mmH ₂ O	135** mmH ₂ O	156** mmH ₂ O
Vertical opening pressure*:	500 mmH ₂ O	530** mmH ₂ O	570** mmH ₂ O
Vertical closing pressure*:	300** mmH ₂ O	340** mmH ₂ O	360** mmH ₂ O

*) +/- 15% **) Modeled value
 - Values measured from bottom of pipe.
 - Tests performed at room temperature (16-20°C).

Max Flow	m/s	l/s
	4	3464

- Higher flows requires custom valve, contact Wapro
 - Flange installation is highly recommended at flows above 2 m/s



In the submerged case opening pressure [mmH₂O /inH₂O] is the difference between the water level upstream and the water level downstream and in the open-air case to the invert of the pipe. In vertical applications, the vertical opening pressure is measured from the outlet of the WaStop.