

# WASTOP® PLASTIC SERIES

## WaStop 160 PVC

<b>Model Name</b>	WS160PVC
<b>Nominal Diameter</b>	NPS/OD 6
<b>Fasteners mtrl.</b>	AISI 316L
<b>Watertightness</b>	EN 13564
<b>Weight [lb]</b>	4.4
<b>Max. Flow Vel. [fps]</b>	6.6
<b>Max. Flow Vol. [GPM]</b>	634.0

## Product Variants

Art. No	WS160PVC-S2	WS160PVC-S3	WS160PVC-S4
<b>Valve Body mtrl.</b>	PVC	PVC	PVC
<b>Max. Back Pressure [ftH<sub>2</sub>O]</b>	9.8	16.4	26.2
<b>Horizontal Opening [inH<sub>2</sub>O]</b>	8.4	8.9	12.5
<b>Horizontal Closing [inH<sub>2</sub>O]</b>	3.4	3.4	3.8
<b>Submerged Opening [inH<sub>2</sub>O]</b>	6.1	7.1	7.5
<b>Submerged Closing [inH<sub>2</sub>O]</b>	0.9	1.0	1.6
<b>Vertical Opening [inH<sub>2</sub>O]</b>	9.3	10.4	11.4
<b>Vertical Closing [inH<sub>2</sub>O]</b>	4.9	5.5	6.5

