


## **WASTOP® INLINE CHECK VALVE**

## WaStop 290

-	
Model Name	WS290
Nominal Diameter	NPS 12
Fasteners mtrl.	AISI 316L
Gasket Mtrl.	EPDM
Weight [lb]	22.0
Min. ID Host Pipe [in]	11.5
Max. ID Host Pipe [in]	12.1
Max. Flow Vel. [fps]	9.8
Max. Flow Vol. [GPM]	3138.4

## **Product Variants**

Art. No	WS290-S3-316
Valve Body mtrl.	AISI 316L
Max. Back Pressure [ftH <sub>2</sub> O]	16.4
Horizontal Opening [inH2O]	8.6
Horizontal Closing [inH <sub>2</sub> O]	5.2
Submerged Opening [inH <sub>2</sub> O]	5.7
Submerged Closing [inH <sub>2</sub> O]	1.8
Vertical Opening [inH <sub>2</sub> O]	13.2
Vertical Closing [inH <sub>2</sub> O]	7.7



© 2024 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved

Wapro AB Munkahusvägen 103 SE-37431 Karlshamn +46 (0)454 185 10 wapro@wapro.com