

WASTOP® INLINE CHECK VALVE

WaStop 750

| | |
|-------------------------------|-----------|
| Model Name | WS750 |
| Nominal Diameter | NPS 30 |
| Fasteners mtrl. | AISI 316L |
| Gasket Mtrl. | EPDM |
| Weight [lb] | 198.4 |
| Min. ID Host Pipe [in] | 29.7 |
| Max. ID Host Pipe [in] | 30.2 |
| Max. Flow Vel. [fps] | 13.1 |
| Max. Flow Vol. [GPM] | 28023.4 |

Product Variants

| Art. No | WS750-S2-304/316 | WS750-S3-304/316 | WS750-S4-304/316 |
|--|----------------------|----------------------|----------------------|
| Valve Body mtrl. | AISI 304 / AISI 316L | AISI 304 / AISI 316L | AISI 304 / AISI 316L |
| Max. Back Pressure [ftH₂O] | 9.8 | 16.4 | 26.2 |
| Horizontal Opening [inH₂O] | 12.0 | 14.3 | 17.7 |
| Horizontal Closing [inH₂O] | 7.5 | 8.6 | 10.6 |
| Submerged Opening [inH₂O] | 7.3 | 8.5 | 9.6 |
| Submerged Closing [inH₂O] | 2.4 | 2.8 | 3.5 |
| Vertical Opening [inH₂O] | 16.7 | 18.5 | 20.4 |
| Vertical Closing [inH₂O] | 7.1 | 7.9 | 8.7 |

